# DELAWARE COUNTY REGIONAL WASTEWATER DISTRICT DELAWARE COUNTY, INDIANA

# CAMMACK SANITARY SEWER REHABILITATION

JANUARY 2025

#### **BOARD OF TRUSTEES**

BILL WALTERS

DANYEL STRUBLE.

JASON RICHARDS

RAY MAYNARD. VICE PRESIDENT PETE OLSEN. MEMBER RON HENSLEY .MEMBER **MEMBER** BRENDA RAGLAND MEMBER JOSHUA TAULBEE. MEMBER JO BOYCE. ATTORNEY

.PRESIDENT

EXECUTIVE DIRECTOR

LAWRENCEBURG BLOOMINGTON

GENERAL LOCATION MAP



QA/QC BY: CHRIS LIMCACO 01/06/2025 DATE:

INDIANA P.E. No. 10000127

DELAWARE

**CERTIFIED BY** 

COUNTY

ROBERT M. BELLUCCI


01/06/2025 DATE:

C 2024 BY COMMONWEALTH ENGINEERS, INC. ALL RIGHTS RESERVED. REPRODUCTION BY ANY METHOD IN WHOLE OR IN PART WITHOUT PERMISSION IS PROHIBITED

**CONTRACT NO. : S20119** 



Drawing Set Index			
SHEET NUMBER	DRAWING NUMBER	SHEET TITLE	
01	G1	TITLE SHEET	
02	G2	VICINITY MAP AND DRAWING INDEX	
03	G3	GENERAL ABBREVIATIONS LEGENDS SYMBOLS AND NOTES	
04	C1	SEWER REHABILITATION PLAN VIEW	
05	C2	SEWER REHABILITATION PLAN VIEW	
06	MD1	MANHOLE REHABILITATION AND MISCELLANEOUS DETAILS	
07	MD2	MISCELLANEOUS DETAILS	
08	MD3	MISCELLANEOUS DETAILS	



Designed By: Drawn By: Checked By RMB JW CAL Issue Date: Project No: Scale: 01/2025 S0119 AS SHOWN VICINITY MAP AND

DRAWING INDEX

G2

Sheet: 02 OF 08

VICINITY MAP

SCALE: 1"=2000'-0"
0 2000'

#### GENERAL ABBREVIATIONS

GENERAL ABBREVIATIONS					
Α	AIR	FLD	FILTRATE DRAIN		MATERIAL
AB	ANCHOR BOLT	FLG	FLANGE	P/L	PROPERTY LINE
AFF	ABOVE FINISH FLOOR	FL	FLUSHING LINE	POJ	PUSH ON JOINT
ALT	ALTERNATE	FLR	FLOOR	PSF	POUNDS PER SQUARE FOOT
ALUM	ALUMINUM	FM	FORCE MAIN	PSI	POUNDS PER SQUARE INCH
@	AT	FRP	FIBER REINFORCED PLASTIC	PVC	POLYVINYL CHLORIDE
APP.	APPARENT	FT	FEET OR FOOT	PW	POTABLE WATER
ATT	AERATION TANK TRANSFER	FTG	FOOTING	1 VV	TOTABLE WATER
AUTO	AUTOMATIC	FW	FINISHED WATER	R	RECIRULCATION
AVG	AVERAGE	ΓVV	FINISHED WATER	RAD	RADIUS
AVG	AVERAGE	G	CAS		RETURN ACTIVATED SLUDGE
В	DAFFLE		GAS	RAS	
В	BAFFLE	GALV	GALVANIZED	RCP	REINFORCED CONCRETE PIPE
BLDG	BUILDING	GEN	GENERAL	RD	ROOF DRAIN
BM	BENCH MARK	GRD	GROUND OR GRADE	REINF	REINFORCING
BOT	BOTTOM			REQ'D	REQUIRED
BRG	BEARING	HB	HOSE BIBB	R/W (ROW	) RIGHT-OF-WAY
		HORIZ	HORIZONTAL		
CFM	CUBIC FEET PER MINUTE	HP	HORSEPOWER	SAN	SANITARY
CL	CENTERLINE	HW	HOT WATER	SAS	SANITARY SEWER
CO	CLEAN OUT			SCH	SCHEDULE
COL/C	COLUMN	ID	INSIDE DIAMETER	SECT	SECTION
CONC	CONCRETE	IJ	ISOLATION JOINT	SF	SQUARE FEET
COP	COPPER	INV	INVERT	SHT	SHEET
CJ	CONSTRUCTION JOINT	ΙΡ	IRON PIN	SL	SAMPLE LINE
CW	COLD WATER			SOS	STORM SEWER
CY	CUBIC YARD	LAV	LAVATORY	SP	STOP PLATE
		LB	POUND	SQ	SQUARE
D	DRAIN	LL	LIVE LOAD	STD	STANDARD
DEC	DECANT	LLV	LONG LEG VERTICAL	S STL. SS	STAINLESS STEEL
DIA	DIAMETER	LTG	LIGHTING	STL	STEEL
DIM	DIMENSION			SUP	SUPERNATANT
DI	DUCTILE IRON PIPE	MAX	MAXIMUM	SY	SQUARE YARD
DL	DEAD LOAD	MCC	MOTOR CONTROL CENTER	0.	
DSPT	DOWN SPOUT	MGD	MILLIONS GALLONS PER DAY	TOS	TOP OF SLAB
DWG	DRAWING	MH	MANHOLE	TOW	TOP OF WALL
2110	Di William	MIN	MINIMUM, MINUTE	TW	TERTIARY WATER
Е	ELECTRICAL CONDUIT	MJ	MECHANICAL JOINT	TYP	TYPICAL
EA	EACH	1010	WEST IN A VIONE SOLIVI	1 1 1	TTTIOAL
EF	EACH FACE	NC	NORMALLY CLOSED	V	VACUUM OR VALVE
EFFL	EFFLUENT	NG	NATURAL GAS	v VAR	VACION ON VALVE VARIES
EL	ELEVATION	NIC	NOT IN CONTRACT	VAR VERT	
EW	EACH WAY			VERI	VERTICAL
		NO	NORMALLY OPEN	14/	WEID
EX	EXISTING	NO.	NUMBER	W	WEIR
EXF	EXHAUST FAN	NPW	NON-POTABLE WATER	W/	WITH
EXP JP	EXPANSION JOINT	0.0	ON OFNITED	W/O	WITHOUT
_	EU TED	OC	ON CENTER	WAS	WASTE ACTIVATED SLUDGE
F	FILTER	OD	OUTSIDE DIAMETER	WC	WATER CLOSET
FCAR	FLANGED COUPLING ADAPTER,	OPG	OPENING	WH	WATER HEATER
	RESTRAINED	OPP	OPPOSITE	WL	WATER LINE
FD	FLOOR DRAIN			WWF	WELDED WIRE FABRIC
FDN	FOUNDATION	PB	PULL BOX		
FH	FIRE HYDRANT	PE	POLYETHYLENE EXP. JT.	ΥH	YARD HYDRANT

## **GENERAL NOTES**

- 1. ALL PROPERTY AND RIGHT-OF-WAY LINE INFORMATION SHOWN IN DRAWING SET ARE APPARENT AND SHALL NOT BE DEEMED EXACT LOCATIONS, UNLESS OTHERWISE NOTED. INFORMATION WAS OBTAINED VIA "INDIANA ON-LINE" GIS SHAPE FILES.
- 2. EXISTING UTILITY INFORMATION SHOWN IN DRAWING SET, MEETS "ASCE 36-02" QUALITY LEVEL "D", UNLESS OTHERWISE NOTED.
  - UTILITY COORDINATION AND PROJECT DEPICTION OF EXISTING SUBSURFACE UTILITY DATA:

#### **UTILITY QUALITY LEVEL DESCRIPTIONS:**

UTILITY QUALITY LEVEL A - PRECISE HORIZONTAL AND VERTICAL LOCATION OF UTILITIES

OBTAINED BY THE ACTUAL EXPOSURE (OR VERIFICATIONS OF PREVIOUSLY EXPOSED AND

SURVEYED UTILITIES) AND SUBSEQUENT MEASUREMENT OF SUBSURFACE UTILITIES, USUALLY AT

A SPECIFIC POINT. ACCURACY OF LOCATION MATCHES PROJECT SURVEY TOLERANCE.

UTILITY QUALITY LEVEL B - INFORMATION OBTAINED THROUGH THE APPLICATION OF

APPROPRIATE SURFACE GEOPHYSICAL METHODS TO DETERMINE THE EXISTENCE AND

APPROXIMATE HORIZONTAL POSITION SUBSURFACE UTILITIES. THE RELIABILITY OF THIS

INFORMATION IS SURVEYED TO PROJECT CONTROL AND SUBJECT TO ACCURACY LEVELS OF THE

GEOPHYSICAL TOLERANCE DEFINED BY THE PROJECT.

UTILITY QUALITY LEVEL C - INFORMATION OBTAINED BY SURVEYING AND PLOTTING VISIBLE

- ABOVE GROUND UTILITY FEATURES AND CORRELATING QUALITY LEVEL "D" INFORMATION.
- <u>UTILITY QUALITY LEVEL D</u> INFORMATION DERIVED FROM EXISTING RECORDS OR VERBAL RECOLLECTIONS.
- 3. NORTHING AND EASTING COORDINATES SHOWN ON ALL MANHOLE, INLETS, ETC. ARE SHOWN FROM CENTER OF STRUCTURE NOT CASTING, UNLESS OTHERWISE NOTED.
- 4. ALL MANHOLES THAT HAVE PIPE INVERT DIFFERENTIAL OF 2' OR GREATER, SHALL BE CONSIDERED A DROP MANHOLE. CONTRACTOR SHALL REFER TO MISCELLANEOUS DETAILS AND DETAILED SPECIFICATIONS FOR MORE INFORMATION.

## DRAWING SET LEGEN

GENERAL SCHEMATIC LEGEND			<u>ND</u>	<b>HATCHING S</b>	YMBOLS
<u> </u>	QUICK DISCONNECT	σ	BOOSTER PUMP		WALL (PLAN VIEW) IULAR BACKFILL (PROFILE VIEW)
Щ	FLANGED SPOOL SECTION	ARV O—	AIR RELIEF VALVE		OLITION (CONTRACTOR SHALL
PRV	PRESSURE REDUCER VALVE	FM	FLOW METER		ER TO DETAILED SPECIFICATIONS
	FLANGED COUPLING ADAPTER	$\overset{GV}{\triangleright\!$	GATE VALVE	-GRO	UT
Z	BALL CHECK VALVE	FCV	FLOW CONTROL VALVE	CON	CRETE
igotimes	MOTOR ACTUATOR	$\bowtie$	VALVE	- CON	SKETE
×	FLEXIBLE CONNECTION	$\bowtie$	ECCENTRIC PLUG VALVE	- STEE	EL .
SCR	FLANGE FILLER & S.S. MESH SCREEN	u	CHECK VALVE		PACTED GRANULAR BACKFILL OR PACTED FOUNDATION
W V90	90° V-NOTCH WEIR	$\nabla$	INCREASER / REDUCER		, Nerzar Gondanien
<u>M</u>	MAGNETIC FLOW METER	₹BV	BUTTERFLY VALVE	- ABAN	IDONED IN PLACE
Д	ULTRASONIC SENSOR	∃ E	PIPE THROUGH FLOOR / WALL		
<u>C</u>	SUBMERSIBLE PUMP	191	BALL VALVE		
	NEW PIPING AND EQUIPMENT	$\vdash$	BLIND FLANGE OR PLUG		
	EXISTING PIPING AND EQUIPMENT		HOSE BIBB		

EXOHT EXOHT	EXISTING OVERHEAD TELEPHONE LINE
——————————————————————————————————————	EXISTING GAS LINE AND VALVE
EXW EXW	EXISTING WATER LINE AND VALVE
EXF/O EXF/O	EXISTING FIBER OPTIC LINE
EXOHE	EXISTING OVERHEAD ELECTRIC LINE
——————————————————————————————————————	EXISTING BURIED ELECTRIC
	EXISTING NON-POTABLE WATER LINE
—— POT ——— POT ———	EXISTING POTABLE WATER LINE
EXBT	EXISTING BURIED TELEPHONE LINE
— x — x — x — x —	EXISTING FENCE
APP. R/W	APPARENT RIGHT-OF-WAY
APP. P/L	APPARENT PROPERTY LINE
<u> </u>	EDGE OF ROAD
<u></u>	EDGE OF ROAD WITH CURB
— — — <del></del>	EXISTING MAJOR CONTOUR LINE
	EXISTING MINOR CONTOUR LINE
— w — — w —	NEW WATER LINE
785	PROPOSED MAJOR CONTOUR LINE
784	PROPOSED MINOR CONTOUR LINE

.EG	<u>END</u>		
0	AC UNIT	1	TELEPHONE MANHOLE
0	BOLLARD	$\Diamond$	TELEPHONE LINE MARKER
$\Diamond$	BOULDER / LARGE ROCK	TR	TRAFFIC MANHOLE
⊠CL	CENTER LINE MONUMENT	<b>₩</b>	WATER LINE MARKER
⊠RW	ROW MONUMENT	<b>(W)</b>	WATER METER
<b>\Phi</b>	CONTROL POINT / BENCH MARK	₩V	VALVE
$\odot$	DRILL HOLE	×	IRRIGATION CONTROL VALVE
MB	MAIL BOX	Q	FIRE HYDRANT
Ø	FLAG POLE	F	FLUSH HYDRANT
0	POST	$\varnothing$	YARD HYDRANT
0	STUMP	N	WALL SPIGOT
<b>(3</b>	BUSH / HEDGE	_	EXISTING PIPE PLUG
	DECIDUOUS TREE		STORM CATCH BASIN (SQUARE)
	CONIFEROUS TREE		STORM CATCH BASIN (ROUND)
	SIGN		STORM CURB INLET
₫	UTILITY LOCATE FLAG		STORM MANHOLE
© CY	GAS LINE MARKER	S	SANITARY MANHOLE
Ä	GAS VALVE	sv ⊠	SANITARY VALVE
<b>©</b>	GAS METER	•	CLEANOUT
-•	GUY POLE	X	VENT
Ø	POWER POLE	×	NEW VALVE
어	LIGHT POLE	Q	NEW FIRE HYDRANT
$\leftarrow$	GUY WIRE	F	NEW FLUSH HYDRANT
EM	ELECTRIC METER		NEW WET SADDLE AND VALVE BODY
	ELECTRIC PANEL		NEW PLUG
ET	ELECTRIC TRANSFORMER	LS	NEW LINE STOP
$\bigcirc$	HAND HOLE BOX		NEW CUT AND CAP
₽ (F)	FIBER OPTIC MARKER	<b>(S</b> )	NEW SANITARY MH
TP	TEL/TV PEDESTAL		

COMMONTALE ALTHING THE COMMONTALE ALTHING THE STREET A Wealth of resources to master a common goal.

A wealth of resources to master a common goal.

A wealth of resources to master a common goal.

A wealth of resources to master a common goal.

A perfect LOCATIONS IN:

BOOWLING GREEN, KY.

SOUTH BEND, IN.

SOUTH BEND, IN.

ture 01/06/2025

WASTEWATER DISTRICT
DELAWARE COUNTY, INDIANA
CAMMACK SANITARY SEWER

ENGINEERS, INC. ALL RIGHTS
RESERVED. REPRODUCTION
BY ANY METHOD IN WHOLE
OR IN PART WITHOUT
PERMISSION IS PROHIBITED


Know what's below. 811 before you dig.

1-800-382-5544


GENERAL ABBREVIATIONS LEGENDS SYMBOLS AND NOTES


Sheet: Drawing No: G3

FUTURE PIPING AND EQUIPMENT



Sheet: 04 OF 08





Issue Date: Project No: Scale: 01/2025 S0119 AS SHOWN

Sheet: 05 OF 08



## EXISTING MH-1 (SEE DRAWING C1 FOR LOCATION)

FRAME TO BE RESET AND PROPERLY SEALED. CONTRACTOR SHALL INSTALL INTERNAL CHIMNEY SEAL. SURFACE RESTORATION VIA CONCRETE PATCH.



### EXISTING MH-21 (SEE DRAWING C2 FOR LOCATION)

INSIDE DROP PIPE TO BE INSTALLED ON THE LATERAL. REFER TO DETAIL, LOWER RIGHT OF THIS DRAWING. CONTRACTOR SHALL REMOVE EXISTING STEPS.




## EXISTING MH-14 (SEE DRAWING C1 FOR LOCATION)

INSIDE DROP PIPE TO BE INSTALLED ON THE UPPERMOST INFLUENT PIPE FROM THE EAST. REFER TO DETAIL, LOWER RIGHT OF THIS DRAWING. CONTRACTOR SHALL REMOVE EXISTING STEPS.



### EXISTING MH-15 (SEE DRAWING C1 FOR LOCATION)

INSIDE DROP PIPE TO BE INSTALLED ON THE UPPERMOST INFLUENT PIPE FROM THE EAST. REFER TO DETAIL, LOWER RIGHT OF THIS DRAWING. CONTRACTOR SHALL REMOVE EXISTING STEPS. FRAME TO BE RESET AND PROPERLY SEALED. CONTRACTOR SHALL INSTALL INTERNAL CHIMNEY SEAL.




#### INSIDE DROP INTO EXISTING MANHOLE

NO SCALE

COMMONWEALTY
ENGINEERS, INC
Awealth of resources to master a common goal.


https://commonwealthengineers.com/
OFFICE LOCATIONS IN:

INDIANAPOLIS, IN. (2)
EVANSVILLE, IN.
FORT WAYNE, IN.
CROWN POINT, IN.
CROWN POINT, IN.



01/06/2025 Date

DELAWARE COUNTY, INDIANA
CAMMACK SANITARY SEWER




Drawing No:

REHABILITATION AND MISCELLANEOUS


DETAILS

Sheet: 06 OF 08

File: Z.\SHARED\IN CLIENTS A-L\DELAWARE COUNTY RWD\D S20119 CAMMACK SANITARY SEWER REHAB\06 CAD\A CURRENT FILES\1 DRA Saved: 1/2/2025 8:28:15 AM Plotted: 1/2/2025 8:29:35 AM Current User: Josh Wheatley LastSavedBy: JWheatley




## SURFACE RESTORATION DETAIL FOR GRAVEL PAVEMENT - ROAD



NOTE: ALL ROAD RESTORATION WITHIN THE COUNTY RIGHT-OF-WAY SHALL HAVE 8" (INCHES) OF CONCRETE. USE RIGHT-OF-WAY PERMIT REQUIREMENTS IN PART 7 OF THE PROJECT SPECIFICATIONS.


## SURFACE RESTORATION DETAIL FOR CONCRETE PAVEMENT - DRIVE

SCALE: NTS




TO COVER DISTURBED AREA SEED AND MULCH COVER (AS SPECIFIED) - EXISTING SURFACE - TOPSOIL -**EXCAVATED** TRENCH WIDTH - SELECTED EXCAVATED MATERIAL

#### SURFACE RESTORATION DETAIL FOR GRASS AREAS SCALE: NTS



SURFACE RESTORATION DETAIL FOR ASPHALT PAVEMENT - ROAD SCALE: NTS



W= MAXIMUM ALLOWABLE TRENCH WIDTH FOR PIPE AS PER ASTM NOT TO EXCEED FOUR (4) FEET FOR 6" THROUGH 24" PIPE NOT SIX (6) FEET FOR 27" THROUGH 48" PIPE

CLASS I OR II MATERIALS

3" MIN. (BELOW THE BELL)

D= PIPE DIAMETER (INTERNAL) Bc= PIPE DIAMETER (EXTERNAL)

NOTES:

1. COMPACTED BEDDING STOPS AT SPRING-LINE OF THE PIPE. BACKFILLING

1. COMPACTED BEDDING STOPS AT SPRING-LINE OF THE SPECIFICATIONS ABOVE THIS POINT SHALL BE IN ACCORDANCE WITH THE SPECIFICATIONS AND AS REQUIRED HEREIN.

2. WHEN CLASS I MATERIAL IS USED FOR BEDDING COMPACTION MAY BE


ACCOMPLISHED BY HAND OR MECHANICAL TAMPING

ACCOMPLISHED ONLY BY HAND OR MECHANICAL TAMPING TO A MIN. OF 95% STANDARD PROCTOR DENSITY.

3. WHEN CLASS II MATERIAL IS USED FOR BEDDING, COMPACTION SHALL BE

4. WORK FALLING UNDER THE JURISDICTION OF THE INDIANA DEPARTMENT OF TRANSPORTATION (INDOT) SHALL UTILIZE COMPACTED GRANULAR BACKFILL MATERIAL FOR INITIAL AND FINAL BACKFILL ANYWHERE WITHIN 12 FEET OF THE EDGE OF PAVEMENT. FOR ALL OTHER NON-INDOT PAVEMENT AREAS (INCLUDING BOTH HARD SURFACED AND COMPACTED AGGREGATE), COMPACTED GRANULAR BACKFILL MATERIAL SHALL BE USED WITHIN 5 FEET OF THE EDGE OF THE PAVEMENT.

TRENCH DETAIL FOR RIGID CONDUITS
NO SCALE



PIPE DEFECT

PIPE REPLACEMENT DETAIL
NO SCALE

Designed By: Drawn By: Checked By RMB JW ssue Date: Project No: Scale:

No. 10000127 STATE OF

MISCELLANEOUS **DETAILS** 

S0119 AS SHOWN

01/2025


MD2

Sheet: 07 OF 08

ADJUSTING RING DETAIL

PLAN VIEW SCALE: 1 1/2"= 1'-0

EXTRUDABLE PREFORMED GASKET MATERIAL IN KEYWAY (SEE GASKET DETAIL ABOVE) —



#### **SPECIFICATIONS EFFECTIVE LIFE**

THE FUNCTIONAL LIFE OF AN EROSION CONTROL BLANKET IS DEPENDENT ON THE MATERIALS USED.

#### ANCHORING

• STAPLES, PINS OR STAKES USED TO PREVENT MOVEMENT OR DISPLACEMENT OF BLANKET. (FOLLOW MANUFACTURER'S RECOMMENDATIONS FOR SPECIFIC APPLICATIONS.)

#### MATERIALS

 ORGANIC (STRAW, EXCELSIOR, WOVEN PAPER, COCONUT FIBER, ETC.) OR SYNTHETIC MULCH INCORPORATED WITH A POLYPROPYLENE, NATURAL FIBER OR SIMILAR NETTING MATERIAL. (THE NETTING MAY BE BIODEGRADABLE, PHOTODEGRADABLE OR PERMANENT.)

NOTE: SOME EROSION CONTROL BLANKET NETTINGS MAY POSE A THREAT TO CERTAIN SPECIES OF WILDLIFE IF THEY BECOME ENTANGLED IN THE NETTING MATRIX.

• SIX TO 12-INCH STAPLES, PINS, OR STAKES.

- 1. SELECT THE TYPE AND WEIGHT OF EROSION CONTROL BLANKET TO FIT THE SITE CONDITIONS (E.G., SLOPE, CHANNEL, FLOW VELOCITY) PER THE MANUFACTURER'S RECOMMENDATIONS.
- 2. PREPARE THE SEEDBED, ADD SOIL AMENDMENTS, AND PERMANENTLY SEED THE AREA IMMEDIATELY FOLLOWING SEEDBED PREPARATION.
- 3. LAY EROSION CONTROL BLANKETS ON THE SEEDED AREA SO THAT THEY ARE IN CONTINUOUS CONTACT WITH THE SOIL WITH EACH UP-SLOPE OR UP-STREAM BLANKET OVERLAPPING THE DOWN-SLOPE OR DOWN-STREAM BLANKET BY AT LEAST EIGHT INCHES, OR FOLLOW MANUFACTURER'S RECOMMENDATIONS.
- 4. TUCK THE UPPERMOST EDGE OF THE UPPER BLANKETS INTO A CHECK SLOT (SLIT TRENCH), BACKFILL WITH SOIL AND TAMP DOWN. IN CERTAIN APPLICATIONS, THE MANUFACTURER MAY REQUIRE ADDITION CHECK SLOTS AT SPECIFIC LOCATIONS DOWN SLOPE FROM THE UPPERMOST EDGE OF THE UPPER BLANKETS.
- ANCHOR THE BLANKETS IN PLACE BY DRIVING STAPLES, PINS, OR STAKES THROUGH THE BLANKET AND INTO THE UNDERLYING SOIL. FOLLOW AN ANCHORING PATTERN APPROPRIATE FOR THE SITE CONDITIONS AND AS RECOMMENDED BY THE MANUFACTURER.


#### **MAINTENANCE**

- INSPECT WITHIN 24 HOURS OF EACH RAIN EVENT AND AT LEAST ONCE EVERY SEVEN CALENDAR DAYS.
- CHECK FOR EROSION OR DISPLACEMENT OF THE BLANKET.
- IF ANY AREA SHOWS EROSION, PULL BACK THAT PORTION OF THE BLANKET COVERING THE ERODED AREA, ADD SOIL AND TAMP, RESEED THE AREA, REPLACE AND STAPLE THE BLANKET.

CHANNEL LININGS UTILIZE STAPLE PATTERN "C" WITH ADDITIONAL STAPLES ON SIDE SLOPES AT PROJECTED WATER LINE.

STAPLE PATTERNS APPLY TO ALL NORTH AMERICAN GREEN EROSION CONTROL BLANKETS. STAPLE PATTERNS MAY VARY DEPENDING UPON SOIL TYPE AND AVERAGE RAINFALL.

AT SLOPE LENGTHS GREATER THAN 300 FEET OR WHERE DRAINAGE OVER LARGE AREAS IS DIRECTED ONT THE BLANKETS, STAPLE PATTERN "C" SHOULD BE UTILIZED.



- INSPECT DAILY, AND AFTER EACH STORM EVENT OR HEAVY USE.
- RESHAPE AS NEEDED FOR DRAINAGE AND RUNOFF CONTROL.
- TOPDRESS WITH CLEAN STONE AS REQUIRED. MAINTAIN MINIMUM DEPTH THROUGHOUT CONSTRUCTION.
- IMMEDIATELY REMOVE MUD AND SEDIMENT TRACKED OR WASHED ONTO PUBLIC ROADS BY SWEEPING OR BRUSHING. (DO NOT FLUSH AREA WITH WATER UNLESS WATER IS CONVEYED TO SEDIMENT TRAP.)
- REPAIR ANY BROKEN PAVEMENT IMMEDIATELY.

STABILIZED CONSTRUCTION ENTRANCE DETAIL


FLOW

- POST 18" DEEP

- SLOPE GRADE

TO DRAIN

(MIN.)



**INSERT (BASKET) INLET** PROTECTION DETAIL NO SCALE

#### - NOMINAL 2"x2" POST MIN. 18" DEPTH INTO SOIL WOOD LATHE STRIP TO SANDWICH FABRIC AS NEEDED -GEOTEXTILE **FABRIC ABOVE** GROUND STAPLE MATERIAL TO POST COMPACTED SOIL OVER MATERIAL TRENCH SIDE TIE BACK BETWEEN GENERAL NOTES: FENCE POST AND SILT FENCES SHOULD BE INSTALLED PRIOR TO ANCHOR -MAJOR SOIL DISTURBANCE. 2. FENCES SHALL BE INSTALLED BETWEEN THE ANCHOR STAKE TRENCH AND ANY DRAINAGE DITCHES OR SWALES. 18" MIN. — MATERIAL EXTENDED 3. FENCES SHALL ALSO BE INSTALLED AROUND THE INTO TRENCH STOCKPILED SOILS.

THE GEOTEXTILE SHALL BE FREE FROM DEFECTS,

TEARS, PUNCTURES, FLAWS, DETERIORATION OR

DAMAGE INCURRED DURING MANUFACTURE, TRANSPORTATION, STORAGE, OR INSTALLATION.

TIE BACKS SHALL BE PLACED AS REQUIRED.

**EROSION CONTROL BLANKET** 

2" X 2" WOOD OR STEEL FENCE POST W/ PROJECTION TO FASTEN FABRIC POST 18" - SPACING 6' O.C. DEEP (MIN.) FILTER FABRIC -WOVEN OR NON-WOVEN -NO JOINTS ALONG LENGTH -STAPLE OR WIRE TO POSTS -(AND WIRE FENCE IF USED) 8"D X 4"W TRENCH TO BE BACKFILLED **GRATE INLET** AND COMPACTED **DOWNSLOPE** FILTER FABRIC BRACING AS -REQUIRED PLAN VIEW 

THE BOTTOM 1' OF THE FENCE SHALL BE BURIED IN THE TRENCH ON THE UPSLOPE SIDE.

- PORTION IMMEDIATELY. REMOVE DEPOSITED SEDIMENT WHEN IT REACHES HALF THE HEIGHT OF THE FENCE, OR IT IS
- CAUSING THE FABRIC TO BULGE.


### STORM INLET WITH SILT FENCE EROSION DETAIL NOT TO SCALE


**SECTION A-A** 

STORM PIPE



- ALL EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE IN ACCORDANCE WITH THE INDIANA STORM WATER QUALITY MANUAL FROM THE INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT AND LOCAL EROSION AND SEDIMENT CONTROL ORDINANCE, OR SWCD.
- 2. THE NOTICE OF INTENT (NOI) AND PUBLIC NOTICE FOR THE PROJECT SHALL BE POSTED ON A SIGN INSTALLED AT OR NEAR THE SITE CONSTRUCTION TRAILER. THE NOI SHALL LIST THE CONTACT INFORMATION FOR THE SITE CONTACT PERSON. THE SIGN AND INFORMATION SHALL BE MAINTAINED AND REMAIN LEGIBLE THROUGHOUT CONSTRUCTION.
- 3. A COPY OF THIS EROSION AND SEDIMENT CONTROL PLAN AND THE EROSION AND SEDIMENT CONTROL REPORT SHALL BE AVAILABLE AT THE PROJECT SITE THROUGHOUT THE ENTIRE CONSTRUCTION PERIOD.
- 4. THE CONTRACTOR SHALL CONTROL WASTE, GARBAGE, DEBRIS, WASTEWATER, AND OTHER SUBSTANCES ON THE SITE SO THEY WILL NOT BE TRANSPORTED FROM THE SITE BY THE ACTION OF WIND, STORM WATER RUNOFF, OR OTHER FORCES. PROPER DISPOSAL OR MANAGEMENT OF ALL WASTES AND UNUSED BUILDING MATERIAL APPROPRIATE TO THE NATURE OF THE WASTE OR MATERIAL IS REQUIRED.
- 5. PUBLIC OR PRIVATE ROADWAYS SHALL BE KEPT CLEAR OF ACCUMULATED SEDIMENT. ALL SEDIMENT THAT IS CLEARED MUST BE RETURNED TO THE LIKELY POINT OF ORIGIN OR OTHER SUITABLE LOCATION. CLEARING OF LARGE AMOUNTS OF SEDIMENT SHALL NOT INCLUDE FLUSHING THE AREA WITH WATER.
- 6. MINIMIZE THE EXPOSURE OF BARE EARTH BY LIMITING THE WORK AREA TO THAT NECESSARY TO PERFORM THE WORK, AND BY PROPER SCHEDULING OF MANPOWER AND EQUIPMENT.
- 7. ALL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE INSPECTED, CLEANED, AND MAINTAINED FOLLOWING EACH STORM EVENT.
- 8. WHEREVER POSSIBLE, MAINTAIN EXISTING VEGETATIVE COVER. USE NON-VEGETATIVE MATERIAL INCLUDING MULCH, EROSION BLANKETS, OR STONE TO CONTROL EROSION FROM DISTURBED AREAS.
- 9. A LOG SHALL BE MAINTAINED OF ALL INSPECTIONS (WEEKLY, AND FOLLOWING STORM EVENTS), MAINTENANCE AND REPAIR OF EROSION AND SEDIMENT CONTROL MEASURES. THE LOG SHALL BE MAINTAINED ON SITE AND BE AVAILABLE UPON REQUEST TO THE OWNERS REPRESENTATIVES AND THE OPERATING AUTHORITIES HAVING JURISDICTION OVER THE SITE.





**MISCELLANEOUS** DETAILS

Sheet: 08 OF 08

SILT FENCE DETAIL

2. FENCE SHALL BE INSTALLED ALONG LEVEL GRADES, NOT ACROSS FLOW CHANNELS.

3. IF OPTIONAL SUPPORT WIRE FENCE IS USED, POST SPACING MAY BE EXTENDED TO 8' O.C.

- INSPECT SILT FENCE PERIODICALLY (WEEKLY) AND AFTER EACH STORM EVENT. IF FABRIC IS TORN OR DAMAGED OR IN ANY WAY BECOMES INEFFECTIVE, REPLACE THE AFFECTED
- 4. TAKE CARE NOT TO UNDERMINE THE FENCE DURING SEDIMENT REMOVAL
- 5. AFTER THE CONTRIBUTING AREA HAS BEEN STABILIZED, REMOVE THE FENCE AND REMAINING SEDIMENT, BRING THE DISTURBED AREA TO GRADE, AND STABILIZE.